

LED PREMIUM VERSION OF THE ORIGINAL FLUORESCENT CIRCULINE LIGHT SURFACE MOUNT FIXTURES

Thin-Lite's Circuline series offer years of reliable, virtually maintenance free service while delivering maximum light output at minimal amp draw. Designs are complemented by opaque white or acrylic diffuser lenses, white powder coated aluminum housings, and attractive wood grain trim.

Model LED109CP and Model LED109CXLP have round housings.

Model LED 109SP is supplied with square housing.

One Touch dimming switch with unlimited dimming levels, Patented "Memory Set" technology retains user programmed brightness settings.

LED life of 100,000 Hrs., Wide Voltage Range Input of 8-30 VDC, Over Voltage Protection that resets at 28 VDC are standard. Color Rendering Index (CRI) 90.

Warranty: 3 years.

Also Available in Fluorescent.



Model No. LED 109SP				LED109CP, LED109CXLP, LED109CAXLP		
Color Temperature	**3000K	4000K	5000K	**3000K	4000K	5000K
Watts	0/9.6			0/9.6		
No. of LEDs	48			48		
Amp Draw @12VDC	0/0.80			0/0.80		
Equivalent Lumens	0/1785	0/1920	0/2304	0/1785	0/1920	0/2304
Dimensions	9.5" Square X 1.75"			9.5" Dia. X 1.75"		
Weight	0.70 lbs.			0.70 lbs.		
Lens P/N	D-109S			D-109C, D-109CXL, D109CAXL		
Case Qty:	20			20		

^{**3000}K Special Orders only.

