

LED PREMIUM VERSION OF THE 130 SERIES SURFACE MOUNT FIXTURES

Thin-Lite's LED 130 series features powder coated aluminum housings and acrylic diffuser lens. They deliver even, non-glare, lighting to ensure a stress free work environment. No hot-spots or eye strain. Decorative Cracked Ice lenses and gold housings are supplied on Model 130CI and Model 134CI. One Touch dimming switch with unlimited dimming levels, Patented "Memory Set" technology retains user programmed brightness settings.

LED life of 100,000 Hrs., Wide Voltage Range Input of 8-30 VDC, Over Voltage Protection that resets at 28 VDC are standard.

Color Rendering Index (CRI) 90.



Model No. LED 130WP, LED 130CIP, LED 130WCIP				LED134VVP, LED134CIP, LED134VVCIP			LED138VVP, LED138GP		
Co l or Temperature	**3000K	4000K	5000K	**3000K	4000K	5000K	**3000K	4000K	5000K
Watts		0/9.6		0/14.4			0/19.2		
No. of LEDs	48			72			96		
Amp Draw @12VDC	0/0.80			0/1.25			0/1.25		
Equivalent Lumens	0/1785	0/1920	0/2304	0/2745	0/2880	0/3264	0/3705	0/3840	0/4224
Dimensions	12" L × 5.375"W × 1.75"			18"L × 5.375"W × 1.75"			24"L X 5.375"W × 1.75"		
Weight	0.80 lbs.			1.20 lbs.			1.60 lbs.		
Lens P/N	D-130W, D-130CI			D-134W, D-134CI			D-138W		
Case Qty:	20			10			20		

^{**3000}K Special Orders only.

